UT300A+
Infrared Thermometer

UT300A+ is an economical infrared thermometer. Its compact and simple design makes it easy for users to carry and operate. Designed with high accuracy, high repeatability, quick response, UT300A+ is suitable for measuring the surface temperature of hard-to-reach or dangerous objects.





UT300A+

Specifications	UT300A+
Certificates	**CE, UKCA**
Temperature range (°C)	-20°C~400°C
Temperature range (°F)	-4°F~752°F
Accuracy (°C)	±2.0°C or ±2%
Accuracy (°F)	±4.0°F or ±2%
Repeatability	1°C or 1.0% (2°F or 1.0%)
D:S ratio	10:1
Response time	≤500ms (95% of reading)
Emissivity	0.95
Spectral response	5.5μm~14μm
Laser power	<1mW
Auto power off	8s
Operating temperature	0°C~50°C (32°F~122°F)
Storage temperature	-20°C~60°C (-4°F~140°F)
Operating humidity	<90% RH (non-condensing)
Drop proof	1m

Features
Simple one button operation
Data hold
Backlight
Low battery indication
°C/°F selection

Characteristics	
Standard accessories	Batteries
Power	1.5V battery (LR03) x 2
Display	20 x 24mm
Product size	135 x 94 x 36.5mm
Product net weight	146g
Standard individual packing	Gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	430 x 265 x 300mm
Standard carton gross weight	6.97kg