200W Balcony semi-flexible solar panel

Warranty

- 2 years Manufacturer Warranty

Manufacturing

- Original cell sorting system ensures the best electric cell match
- EL-Testing before packing.
- Comprehensive module power testing.

Performance

- Upgraded efficiency and unprecedented flexibility.
- Weakened hot-spot effect, extremely low risk of micro cracks.
- Special connection method lowers the internal resistance and ensures better performance than traditional connection with busbar.
- IP67 rated junction box, reliable cables and standard MC4 connectors improve the stability



Mechanical Data

Standard Test Conditions AM=1.5, E=1000W/m2, TC=25℃

Nominal Power	200W
Cell Type	Monocrystalline
Model of Cells	210mm
Maximum Power Current (Impp)	7.84A
Maximum Power Voltage (Vmpp)	25.52V
Open-circuit Voltage (Voc)	29.92V
Short-circuit Current (Isc)	8.31A
Maximum System Voltage	200V
Output Tolerance	±3%
Cable	900mm / 2.5mm2
Connector Type	MC4 / MC4 Compatible
Module Structure	CPC/EVA/ Backsheet
Junction box rating	⩾IP67
Diode	√
Working Temperature	-20℃~+65℃

Packaging

Module Dimensions	1260*905*2mm
Module Weight	4.2kg
Package	Single Package
Pieces per Pallet	30
Gross Weight per Pallet	126kg



SOLMAX NEW ENERGY B.V.
Address: Defensiedok 18,3433 KL, Nieuwegein,The Netherlands
Tel:+31-307855708
Email: info25@solarfam.nl